

<b>Category</b>	European Hardened Timber
<b>Type</b>	100% Real Wood - Oak
<b>Plank Size</b>	206mm x 2200mm
<b>Planks per Carton</b>	4pcs / 1.82m <sup>2</sup>
<b>Weight per Carton</b>	11.0kg
<b>Thickness</b>	11.3mm
<b>Top Layer Thickness</b>	0.6mm
<b>Surface Finishing</b>	Pro Matt Lacquer
<b>Core</b>	Ultra HDF
<b>Locking System</b>	Välinge 5G Dry
<b>Slip Resistance</b>	USRV 40 (CE /TS 15676:2008 / EN 14342:2013)
<b>Thermal Resistance</b>	0.07 m <sup>2</sup> K/W (EN 12667)
<b>Thickness Swelling</b>	<10% (EN 14354)
<b>Fire Rating</b>	CRF ≥ 8.8 kW/m <sup>2</sup> (ISO 9239-1) Bfl-s1 (EN 13501-1)
<b>Indoor Air Quality</b>	A+ Emissions / Indoor Air Comfort Gold®
<b>Formaldehyde Group</b>	E1 (EN 717-1)
<b>Wear Resistance</b>	>6000 cycles (EN 14354)
<b>Impact Resistance</b>	EC3 (EN 14354)
<b>Underfloor Heating</b>	Suitable - Maximum Temperature 27°C
<b>Classification</b>	Class 23 Domestic Heavy Class 33 Commercial Heavy
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet) Commercial on Request
<b>Installation</b>	Must be properly installed according to the installation instructions.
<b>Environmental</b>	Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified Greenguard Gold Quality Management ISO 9001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.