



Stain Resistant



Fade Resistant



Environmentally Responsible



Antistatic



Suitable For Underfloor Heating



Suitable For Stairs



Anti-Allergenic



Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	3.66m
Standard Roll Length	30m
Yarn Weight	1560g/m ² / 46oz/yd ²
Total Weight	2560g/m ²
Pile Height	14.0mm
Total Thickness	16.0mm
Machine Gauge	1/8th
Primary Backing	Woven Polypropylene
Secondary Backing	Action Fleece
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 5.2kW/m ² (ASTM E 648-17)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential / Light Duty Commercial
Stair Rating	Suitable
Warranties	10 Year General Warranty 10 Year Residential Wear Warranty 10 Year Stain Resistant Warranty 10 Year Fade Resistant Warranty 10 Year Colourfast Warranty 3 Year Manufacturing Defects Warranty 3 Year Commercial Wear Warranty
Environmental	Low VOC, solution dyeing uses no water, post consumer recycled content, ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.