

Commercial Vinyl Centra 2021

Specifications:



Domestic
heavy




Commercial
very heavy



Industrial
heavy



Slip
resistant




Dimensional
stability



Thermal
resistance



Chemical
resistant



Light
fastness

	<u>Centra 1</u>	<u>Centra 2</u>
Level of use -	23 – 34 - 43	33 - 42
Total thickness -	2.00 mm	2.30 mm
Wear layer -	0.70 mm	0.60 mm
Wear layer PUR treatment -	HyperGuard+	HyperGuard+
Total weight -	2543 g/m ²	2200 g/m ²
Width -	2 m	2 m
Standard length -	25 m	30 m
Inflammability -	Bfl-S1	Bfl-S1
Slip resistance -	DS	DS
Slip restraint -	R10	R10
Residual indentation -	0.05 mm	0.20 mm
Furniture leg resistance -	Very good	Very good
Electrical resistance -	10 ⁹ Ohm	10 ⁹ Ohm
Dimensional stability -	0.05 %	0.10 %
Heat insulation -	0.0080 (m ² .K/W)	0.0108 (m ² .K/W)
Light fastness -	6	6-7
Underfloor heating -	Suitable	Suitable
Resistance to chemicals -	Very good	Very good
Warranty	5 years	5 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

