Residential Vinyl

Concept

Specifications:

















Domestic light

Slip resistant

Reduces

Light

Thermal resistance

Chemical resistant

Stocked in New Zealand

_	
European classification -	21
Total thickness -	1.50 mm
Wear layer -	0.20 mm
Total weight -	1210 g/m ²
Width -	2 m & 3 m
Slip resistance -	R10
Inflammability -	Cfl-S1
Acoustical insulation -	12 dB
Light fastness -	≥ 6
Underfloor heating -	Suitable
Thermal resistance -	$0.02 \text{ m}^2\text{/kW}$
Resistance to household chemicals -	OK
Warranty (year) -	5 years (Residential use)

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz**

