

DECLARATION OF PERFORMANCE N° 08017_1



03/08/2022

Finfloor Durable SUPREME

Manufactured at: Finsa
Fibranor
Políg. Ind. de Rábade
27370 RÁBADE (ESPAÑA)

TECHNICAL CLASS	INTENDED USE	AVCP*	NOTIFIED BODY AND REFERENCE	CERTIFICATE NUMBER
LAMINATED FLOORING	Floor covering for indoor applications	3	AIDIMME- 1981	221.C.1607.092.ES.01

*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011

Finfloor Durable SUPREME

CLASSIFICATION ACCORDING TO EN 685

Rev: 01/03/2022


CARACTERISTIQUES	REQUIREMENT	TEST METHOD
Formaldehyde emissions HCHO	0,11 ppm	CARB PHASE 2/EPA TSCA TITLE VI ASTM E 1333-14
Reaction to fire	Bfl s1	EN 14041 / EN 13501-1 / EN ISO 9239-1 / EN ISO 11925-2
Slip resistance coefficient under dry conditions	Class DS (>=0,3)	EN 14041 / EN 13893
Electrical behaviour	The measurement of the body voltage at 23°C/25% humidity are ≤ 2kV. Fulfils the criterions for the classification as an Antistatic Floor Covering	EN 14041 / EN 1815
Electrical behaviour / vertical resistance	Antistatic Floor "ASF – Class 2" in accordance with the international standard IEC 61340-4- 1:1995	EN 14041 / EN 1815
Thermal Resistance	Without Underlay: 0,06 m ² ·K/W + FINfloor PE Underlay 0,154 m ² ·K/W + Finfloor Silent Underlay 0,127 m ² ·K/W Suitable for warm-water underfloor heating systems	EN 14041 / EN 12664
Antibacterial efficiency	Reduction of bacterial activity in 24 hours ≥ 99.9% according to tests carried out at the IMSL	ISO 22196
CE Certificate	DoP 08017_1	EN 14041

The above information is subject to modifications for the benefit of further improvements.

The performance of the reference product are in compliance with the performance declared above
This Declaration of Performance is issued under the sole responsibility of FINANCIERA MADERERA S.A. (FINSA)

Javier Portela
FINSA R&D + Quality Director

Javier Rodríguez



A circular blue stamp with the text "FINANCIERA MADERERA, S.A." at the top and "SANTIAGO" at the bottom, separated by two small stars on each side.