

TIMBER



Xpert^{pro}

PRODUCT SPECIFICATION	STANDARD	WELLINGTON SPECIFICATION
Width		190mm
Length		1820mm
Pack size		2.075m² (Maximum 4 planks per pack made-up of shorter boards)
Planks per pack		6 planks
Pack weight		19.19kg
Total thickness		14mm nominal
Surface coating		High performance UV cured acrylic lacquer
Surface treatment		Matt finish

PHYSICAL PROPERTY	TEST METHOD	WELLINGTON SPECIFICATION
Construction		3 layers
Colours in range		10 colours
Edge detail		Micro-bevel 2 sides
Grading	EN1310 & EN1311; Internal (vibrant)	Knots <80mm Qty unlimited
Rustic/colour variation		high
Installation method		Floating or glue down
Joining system		Uniclic [®] 4 sides
Moisture content		6-8% MC
Slip resistance	AS 4586:2013	P3
Abrasion group	DIN 68861	100-1050
Fire resistance	AS/ISO 9239.1-2003	4.6 Kw/m² Smoke 13
Thermal resistance		R= 0.147
Electric behaviour		Static free
Indoor air quality	EN717	=0.02mg/m³ (<0.124mg/m³) (large chamber)
Warranty	Domestic use	20 year wear and lifetime structural*
	Commerical Use	Available upon request*

*Warranty details:

XpertPro Timber Flooring warranty terms & conditions are available from place of purchase.

Swatch samples are not fully representative of all the different nuances within each plank. As timber is a natural product, variation should be expected in terms of colour, natural features (knots, cracks etc.), fillers and shade variation should be expected in a finished floor and will often vary from the samples provided.



