

<b>Category</b>	Laminate
<b>Plank Size</b>	194mm x 1331mm
<b>Planks per Carton</b>	8pcs / 2.066m <sup>2</sup>
<b>Weight per Carton</b>	16.1kg
<b>Thickness</b>	8mm
<b>Surface Finishing</b>	Wood Impression
<b>Core</b>	Ultra HDF
<b>Bevel</b>	Micro 4V
<b>Locking System</b>	Angle/Angle
<b>Slip Resistance</b>	DS (EN 14041 / EN 13893)
<b>Thermal Resistance</b>	0.06 m <sup>2</sup> K/W (EN 12667)
<b>Fire Rating</b>	Bfls1 (EN ISO 9239-1)
<b>Indoor Air Quality</b>	A+ Emissions
<b>Abrasion Resistance</b>	AC6 (EN 13329)
<b>Castor Chair Resistance</b>	No damage with Type W (EN 425)
<b>Impact resistance</b>	IC 3 (EN 13329)
<b>Underfloor Heating</b>	Suitable - Maximum Temperature 27°C
<b>Classification</b>	Class 33 Commercial Heavy
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	35 Year Residential Warranty 15 Year Moisture Protection (Kitchen, Laundry, Toilet, Bathroom) Commercial on Request
<b>Installation</b>	Must be properly installed according to the installation instructions.
<b>Environmental</b>	EU Ecolabel Cradle to Cradle Environmental Product Declaration LEED® BREEAM Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.