

# Firenze Collection

**Please note: that there are 3 different datasheets within this range.  
This is due to the thickness of the vinyl.**

## **Range 1 Data Information**

**Width:** 2m & 4m

**Wear Layer:** 0.25mm

**Warranty:** 10 Years

**Slip Resistance:** R10



Havanna Oak 019S



Texas Oak 603M



Texas Oak 620D



Texas Oak 630M



Texas Oak 693D



Havanna Oak 966D



Silk Oak 916L



Silk Oak 979L



### Product Information

Norm	EN ISO 26986			* check individual ref. for available widths
Intensity of use	ISO 10874 (EN 685)		23 Domestic heavy 31 Commercial moderate	class
Total Thickness	EN ISO 24346 (EN 428)		2,50	mm
Wearlayer	EN ISO 24340 (EN 429)		0,25	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1650	g/m <sup>2</sup>
Standard width	EN ISO 24341 (EN 426)		4 *	m
Standard length	EN ISO 24341 (EN 426)		30	m

### Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,35	mm
Impact sound improvement	EN ISO 717/2		Δ Lw 13	dB
Dynamic coefficient of friction	EN 13893		> 0,6	
Slip resistance (ramp test with oil)	DIN 51130		R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1		Bfl/S1	class
Underfloor heating	EN 12667		Suitable	
Thermal resistance	ISO 8302		0,023	m <sup>2</sup> /Kw
Thermal conductivity	EN 12524		0,11	W/(m.K)
Chemical resistance	ISO 16581 (EN 424)		resistant	
Static Electrical Propensity	EN 1815		< 2kV	On concrete

### Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m<sup>3</sup> of air)



100% phthalate free  
\*for all products produced from May 2017 onwards

This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.




Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)



Slovenian plant Certifié  
Slovenian / Belgium plant Certifié

### Product Build

1. PU lacquer
2. Wear layer
3. Design layer
4. Foam layer
5. Impregnation layer
6. Glass fibre interlayer
7. Backing



## Features



# Firenze Collection

***Please note: that there are 3 different datasheets within this range.  
This is due to the thickness of the vinyl.***

## ***Range 2 Data Information***

**Width:** 2m & 3m

**Wear Layer:** 0.20mm

**Warranty:** 5 Years

**Slip Resistance:** R10



Antique Oak 091S



Holm Oak 619M



Holm Oak 969M



Holm Oak 969M

## Product Information

Norm	EN ISO 26986			* check individual ref. for available widths
Intensity of use	ISO 10874 (EN 685)		22 Domestic general use	class
Total Thickness	EN ISO 24346 (EN 428)		2,80	mm
Wearlayer	EN ISO 24340 (EN 429)		0,20	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1500	gr/m <sup>2</sup>
Standard width	EN ISO 24341 (EN 426)		2 - 3 - 4 *	m
Standard length	EN ISO 24341 (EN 426)		30	m

## Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,35	mm
Impact sound improvement	EN ISO 717/2		Δ Lw 16	dB
Dynamic coefficient of friction	EN 13893		> 0,6	
Slip resistance (ramp test with oil)	DIN 51130		R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1		Bfl/S1	class
Underfloor heating	EN 12667		Suitable	
Thermal resistance	ISO 8302		0,030	m <sup>2</sup> /Kw
Thermal conductivity	EN 12524		0,09	W/m.K
Chemical resistance	ISO 26987 (EN 423)		resistant	
Static Electrical Propensity	EN 1815		< 2kV	On concrete

## Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m<sup>3</sup> of air)



100% phthalate free  
\*for all products produced from May 2017 onwards

This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.



Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)



## Product Build

1. PU lacquer
2. Wear layer
3. Design layer
4. Foam layer
5. Impregnation layer
6. Glass fibre interlayer
7. Backing



## Features





# Firenze Collection

***Please note: that there are 3 different datasheets within this range.  
This is due to the thickness of the vinyl.***

## ***Range 3 Data Information***

**Width:** 2m & 3m

**Wear Layer:** 0.15mm

**Warranty:** 5 Years

**Slip Resistance:** R10



Amadora 990D



Lagos 909D



## Product Information

Norm	EN ISO 26986		* check individual ref. for available widths	
Intensity of use	ISO 10874 (EN 685)		22 Domestic General / Medium	class
Total Thickness	EN ISO 24346 (EN 428)		2,80	mm
Wearlayer	EN ISO 24340 (EN 429)		0,20	mm
Abrasion group	EN 660-2		T	class
Total weight	EN ISO 23997 (EN 430)		1600	g/m <sup>2</sup>
Standard width	EN ISO 24341 (EN 426)		2 - 3 - 4 *	m
Standard length	EN ISO 24341 (EN 426)		+/- 30	m

## Technical Information

Dimensional stability	EN ISO 23999 (EN 434)		≤ 0,40	%
Curling	EN ISO 23999		≤ 8	mm
Light stability	EN ISO 105 B02		≥ 6	degree
Residual indentation	EN ISO 24343-1 (EN 433)		≤ 0,35	mm
Impact sound improvement	EN ISO 717/2		ΔLw 16	dB
Dynamic coefficient of friction	EN 13893		> 0,6	
Slip resistance (ramp test with oil)	DIN 51130		R10	scale
Reaction to fire Report number ---- VNLF 031380.4	EN 13501-1		Bfl-s1	class
Underfloor heating	EN 12667		Suitable	
Thermal resistance	ISO 8302		0,025	m <sup>2</sup> K/w
Thermal conductivity	EN 12524		0,10	W/m.K
Chemical resistance	ISO 26987 (EN 423)		resistant	
Static Electrical Propensity	EN 1815		< 2kV	On concrete

## Environment



100% Recyclable.

- No heavy metals
- No solvents
- No Formaldehydes
- No harmful plasticizers



E1 means that the level of formaldehyde is inferior to 0.1ppm (= 0.12 mg/m<sup>3</sup> of air)



100% phthalate free  
\*for all products produced from May 2017 onwards

This is illustrative by the choice of raw materials, of partners, of transport and of fabrication processes. Our selection of core materials is based on a combination of our clients' requirements for a quality product as well as requirements for a minimal impact on the environment. We are the leaders in terms of the implementation of clean renewable energy sources and we actively work towards the constant improvement of energy saving.



Our products are classified as A+ for the emission of volatile substances in inside air (compulsive sanitary labelling in France since January 2012)



## Product Build

1. Wear layer
2. Design layer
3. Foam layer
4. Impregnation layer
5. Glass fibre interlayer
6. Backing



## Features

