

PRODUCT NAME: FLOORSCAPE VINYL HYBRID FLOORING

BPIR DECLARATION

Version: V1 December 2023

DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Floorscape (NZ) Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the [Building \(Building Product Information Requirements\) Regulations 2022](#)

COMPANY DETAILS

Manufacturer Legal and trading name / Address for service	Unilin Group, Ooigemstraat 3 8710, Wielsbeke, West-Flanders, Belgium
Manufacturer Website / Email	https://unilin.com/en aftersales@unilin.com
Importer legal and trading name / Address for service	Floorscape Limited, Unit 3 /19 Triton Drive Auckland 0632
Importer website / email	https://floorscape.co.nz/ sales@floorscape.co.nz
Importer NZBN	9429031816861
Importer phone number	094760428
Sustainability Information	https://unilin.com/en/one-home
Product Code Identifier	HPUCP / TIR / TIRXXL / TID / PUGP / V3531 / V3520

DESCRIPTION OF BUILDING PRODUCT / INTENDED USE

Floorscape Vinyl Hybrid is a floor covering made-up of Plastic, Fibreglass, and Stone-based products depending on the style. Our most innovative styles are made-up of multiple layers: UV-cured Acrylic top-layer, design layer, acoustic layer, fibreglass layers, stability layer, and underlay. All Floorscape Vinyl Hybrid includes our innovative Uniclic® joining system to ensure a tight joint and ease of installation. The full range of Floorscape Vinyl Hybrid product can be found at www.floorscape.co.nz/products/timber-flooring

RELEVANT NEW ZEALAND BUILDING CODE CLAUSES

CLAUSE	EVIDENCE
B2 Durability — B2.3.1 (c)	Floorscape Vinyl Hybrid has durability of over 20 years where installation, and care and maintenance instructions are followed. Durability is proven through achieving the requirement of standard EN16511 : Standard: Loose-laid panels (NZWTA Taber Test certification)
C3 Fire affecting areas beyond the fire source — C3.4 (b)	Floorscape Vinyl Hybrid meets the requirements of C3 through standard ISO9239-1 Reaction to Fire Tests for Floorings. (AWTA test certification)
D1 Access Routes — D1.3.3 (d)	Floorscape Vinyl Hybrid has slip resistant ratings per standard AS4586:2013 Wet Pendulum Slip Resistance Test (ATTAR test certification).
E3 Internal moisture — E3.3.3, E3.3.5, E3.3.6	As an 'Alternative Solution', Floorscape Vinyl Hybrid is proven to be impervious and easy-to-clean through ISO4760 Topical Moisture Resistance – assembled joint (NZWTA test certification), and through the following of care and maintenance instructions. See further detail here: E3 Documentation - Floorscape
F2 Hazardous building materials — F2.3.1	Floorscape Vinyl Hybrid meets the requirements of standard EN717-1 : VOC Emission (Eurofins test certification) Our Vinyl Hybrid product does not contain ortho-phthalates.
G3 Food preparation and prevention of contamination — G3.3.2 (b)	Floorscape Vinyl Hybrid meets this requirement where care and maintenance instructions are followed.
G6 Airborne and impact sound — G6.3.1, G6.3.2	Floorscape Vinyl Hybrid has acoustic certification for standard ISO140-7 : Sound Transmission and Insulation standard (SLR test certification)

Supporting documentation for the above can be found at www.floorscape.co.nz/technical-hub

SCOPE OF USE AND LIMITATIONS

SCOPE	LIMITATION
Can be installed in all general interior areas of a building, including high traffic areas	<ul style="list-style-type: none"> - Remove all existing carpet or soft flooring and underlays - Is not recommended inside showers or saunas - Not suitable for exterior use - The floor must be able to move freely - All subfloors need to be sound and structurally stable enough to be installed atop. Any loose parts of the subfloor or hard flooring need to be secured, repaired, or removed and replaced. Subfloor must be flat with no unevenness greater than 2mm over the length of 1 metre in any direction. Clean and free of

	<p>old adhesives, building rubble etc prior to installation. Concrete subfloors must test below 80%RH. Timber subfloors must test below 14%MC.</p> <p>- See Installation & Care and Maintenance Instructions for further information www.floorscape.co.nz/technical-hub</p>
Suitable for Underfloor Heating systems	<p>- See Underfloor Heating System Instructions www.floorscape.co.nz/installation/hybrid-installation</p>
Suitable for Wet Areas (E.g., Bathroom, Toilet, Laundry, Kitchen)	<p>- Suitable for use in wet areas if specific installation requirements are met as detailed here: www.floorscape.co.nz/installation/hybrid-installation</p>

Supporting documentation including Installation instructions, Care and Maintenance instructions, and warranty information can be found at www.floorscape.co.nz/technical-hub

RESPONSIBLE PERSON

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Floorscape Vinyl Hybrid is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of Floorscape Limited:



Mike Caird
 GENERAL MANAGER SALES & MARKETING
 23 November 2023