

Grande Ultimo



Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Grande Ultimo

Grande Ultimos' multi-layer structure makes it durable and resilient against temperature changes. Its natural wood design with minimal pattern repeat brings a touch of nature indoors. Easy installation is a plus, while its soft feel, warmth, and noise reduction create an inviting atmosphere. With recycled content and low impact manufacturing in Belgium, this is a floor that takes its responsibility to the planet seriously.

Technical Data

Type:	Vinyl Plank Flooring	Country of Origin:	Belgium
Dimensions:	1320mm x 196mm	Finish:	Matte
Total Product Thickness:	2.5mm	Surface:	Embossed 'grip' texture
Wear Layer:	0.55mm	Profile:	4-Sided Bevel
Units Per Box:	14 boards	Coating System:	Superguard®
m² per box:	3.62	Installation Method:	Direct Stick
Colours:	12		

Performance

Dimensional Stability:	(ISO 23999) Norm: ≤ 1,0,25 l % Average result measured: ≤ 10,05l %	Impact Sound Reduction:	(EN ISO 717-2) 4 dB
Thermal Resistance:	(EN 12667) R=0,018m²K/W	Light Fastness:	(EN ISO 105-B02) ≥6
Thermal Conductivity:	(EN ISO 10456) 0,25 W/(m.K)	Flammability:	(EN ISO 9239) CRF 9.4kW/m²
Classification:	(EN ISO 10874) Residential 23, Commercial 33, Industrial 42	Smoke Value:	(EN ISO 9239) 109% minutes
Abrasion Rating:	(EN ISO 660-2) Class T	Slip Resistance:	(AS/NZ 4586-2013) P2, R10
E3 Internal Moisture:	3.0 Watersplash - Alternative solution	Castor Chair:	(EN ISO 4918) No damage to wearlayer, no delamination
Suitable for Wet Areas:	All wet areas - subject to proper installation and maintenance	Residual Indentation:	(EN ISO 24343-1) Norm: ≤ 0,10mm Average result measured: 0,03mm
Topical Moisture Resistance:	(ISO4760) No penetration through assembled joint		

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Matte Finish



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Mid Range



0.55mm Wear Layer



4 Sided Bevel



Wear Resistant



European Made



Easy To Clean

Grande Ultimo



Waterproof Surface[^]



Global Green Tag