



|                            |  |
|----------------------------|--|
| Construction               | Tufted Cut Pile Carpet   |
| Yarn                       | 100% Solution Dyed Nylon   |
| Width                      | 3.66m  |
| Standard Roll Length       | 25m  |
| Yarn Weight                | 1966g/m <sup>2</sup> / 58oz/yd <sup>2</sup>  |
| Total Weight               | 2976g/m <sup>2</sup>   |
| Pile Height                | 14.0mm   |
| Total Thickness            | 16.0mm   |
| Machine Gauge              | 1/8th  |
| Primary Backing            | Woven Polypropylene  |
| Secondary Backing          | Action Fleece  |
| Electrical Properties      | Antistatic   |
| Electrical Propensity      | ≤ 2kV  |
| Fire Rating                | CRF 5.8kW/m <sup>2</sup> (ISO 9239-1)  |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew.  |
| Underfloor Heating         | Suitable   |
| Rating                     | Extra Heavy Duty Residential / Medium Duty Commercial  |
| Stair Rating               | Suitable   |
| Warranties                 | <b>10 Year Living Warranty</b><br>10 Year Residential Wear Warranty<br>10 Year Stain Resistant Warranty<br>10 Year Fade Resistant Warranty<br>10 Year Colourfast Warranty<br>10 Year Manufacturing Defects Warranty<br>5 Year Commercial Wear Warranty     |
| Environmental              | Low VOC, solution dyeing uses no water, post consumer recycled content, ISO 14001  |
| Installation               | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>All seams must be sealed.<br>Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or [belgotex.co.nz](http://belgotex.co.nz)
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.