



Softology

S201



| | |
|----------------------------|--|
| Construction | Tufted Cut Pile Carpet |
| Yarn | 100% Premium Soft Solution Dyed Nylon |
| Width | 4.0m |
| Standard Roll Length | 25m |
| Yarn Weight | 1150g/m ² / 33.9oz/yd ² |
| Total Weight | ±2124g/m ² |
| Pile Height | 10.5mm |
| Total Thickness | 11.5mm |
| Machine Gauge | 1/8th |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Fusion Bac |
| Electrical Properties | Antistatic |
| Electrical Propensity | < 2kV (EN 1307 / ISO 6356) |
| Fire Test | ISO 9239-1 |
| VOC Rating | Pass (GBCSA/GLP Criteria) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Underfloor Heating | Suitable - Maximum Temperature 37°C |
| Rating | Heavy Duty Residential |
| Stair Rating | Suitable |
| Warranties | 15 Year Premium Warranty 15 Year Residential Wear Warranty 20 Year Stain Proof Warranty 20 Year Fade Proof Warranty 20 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty |
| Environmental | Low VOC, solution dyeing uses no water, Eco-Wash™ Treatment ISO 14001, Greentag Certified |
| Installation | Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |

- For samples, range and warranty details please contact us on 0800 377 753 or www.irvineflooring.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Vacuum cleaners should have 'high suction' and no beater brush.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.