Residential Vinyl

Zenith

Specifications:

















Domestic medium

Natural

Slip resistant

Reduces

Thermal resistance

Long

Great for

Stocked in New Zealand

European classification -	22
Total thickness -	1.70 mm
Wear layer -	0.20 mm
Wear layer treatment -	Natural Feel
Total weight -	1400 g/m ²
Width -	2 m & 3 m
Standard length -	35 m
Slip resistance -	R10
Inflammability -	Bfl-S1
Acoustical insulation -	16 dB
Underfloor heating -	Suitable
Thermal conductivity -	0.25 W / mK
Thermal resistance -	0.0068 m ² K/W
Resistance to household chemicals -	Very good
Warranty (year) -	5 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz**

